Company Name <u>Decker Electric</u> , <u>Inc</u>		
PLYWOOD CO	VERS ON FL	OOR OPENINGS
Safely covering a floor opening with a piece of plywood down. Total safety on the job means a total job of elimina hazards can result only in half, inadequate or incomplete	ating the hazard. Ha	alf a jobinadequate or incomplete jobs of covering hole
	s it up, takes a step	we calls down to a laborer to hand him a sheet of plywood or two forward in the act of standing the plywood up, and disabling injuries. Why did it happen?
Although originally nailed down with concrete nails, a sr adequately. Traffic over it, springing the plywood, looser		od over the hole wasn't large enough to overlap it
The plywood over the hole wasn't marked in any way. The loose material laying on the floor.	nere was no warning	g of any kind on it. The person mistook it for a piece of
The person wasn't told about it. The laborer was not mad calculated to prevent accidents. Nor was the laborer told		
Anything less than total safety is no safety at all. The total	al safety attitude mu	ast be kept in mind when floor openings are being covered
When covering floor openings:		
1. The hole should be covered securely, with a cover big enough and rigid enough to prevent failure.		
2. It should be painted, labeled or marked with a danger of	or warning "DO NO	OT REMOVE".
3. Every employee on the job should be warned about it.		
Safety Recommendations:		
Job Specific Topics:		
M.S.D.S Reviewed:		
Attended By:		