

ArgonSafety Data Sheet E-4563

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 08-03-2016 Supersedes: 10-15-2013

SECTION 1: Identification

1.1. Product identifier

Product form : Substance
Name : Argon
CAS No : 7440-37-1
Formula : Ar

Other means of identification : Shielding gas, Argon 40

Product group : Core Products

1.2. Recommended use and restrictions on use

Recommended uses and restrictions : Industrial use

1.3. Supplier

Praxair Canada inc. 1200 – 1 City Centre Drive Mississauga - Canada L5B 1M2 T 1-905-803-1600 - F 1-905-803-1682 www.praxair.ca

1.4. Emergency telephone number

Emergency number : 1-800-363-0042

Call emergency number 24 hours a day only for spills, leaks, fire, exposure, or accidents

involving this product.

For routine information, contact your supplier or Praxair sales representative.

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

GHS-CA classification

Simple asphyxiant H380 Compressed gas H280

2.2. GHS Label elements, including precautionary statements

GHS-CA labelling

Hazard pictograms



Signal word : WARNING

Hazard statements : CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED

MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION

Precautionary statements : Do not handle until all safety precautions have been read and understood Use and store only outdoors or in a well-ventilated area

Protect from sunlight when ambient temperature exceeds 52°C (125°F)

Use a back flow preventive device in the piping Close valve after each use and when empty Use only with equipment rated for cylinder pressure

2.3. Other hazards

Other hazards not contributing to the

classification

: Asphyxiant in high concentrations.

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.

EN (English) SDS ID : E-4563 1/7



Safety Data Sheet E-4563

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 08-03-2016 Supersedes: 10-15-2013

Unknown acute toxicity (GHS-CA)

No data available

SECTION 3: Composition/information on ingredients

Substances

Name	CAS No.	% (Vol.)	Common Name (synonyms)
Argon (Main constituent)	(CAS No) 7440-37-1	100	Argon, compressed

Mixtures

Not applicable

SECTION 4: First-aid measures

Description of first aid measures

First-aid measures after inhalation

: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

First-aid measures after skin contact

: Adverse effects not expected from this product.

First-aid measures after eye contact

: Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. Contact an ophthalmologist immediately. Get immediate medical attention.

: Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects (acute and delayed)

No additional information available

First-aid measures after ingestion

Immediate medical attention and special treatment, if necessary 4.3.

Other medical advice or treatment : None.

SECTION 5: Fire-fighting measures

Suitable extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media

No additional information available

5.3. Specific hazards arising from the hazardous product

Reactivity : No reactivity hazard other than the effects described in sub-sections below.

: No reactivity hazard other than the effects described in sub-sections below. Reactivity in case of fire

Special protective equipment and precautions for fire-fighters

Firefighting instructions

: Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with their provincial and local fire code regulations.

Protection during firefighting

: Compressed gas: asphyxiant. Suffocation hazard by lack of oxygen.

Special protective equipment for fire fighters

Use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.

Specific methods

Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas containers to rupture. Cool endangered containers with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems

Stop flow of product if safe to do so

Use water spray or fog to knock down fire fumes if possible.

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.

SDS ID: E-4563 EN (English) 2/7



Argon

Safety Data Sheet E-4563

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 08-03-2016 Supersedes: 10-15-2013

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Evacuate area. Ensure adequate air ventilation. Wear self-contained breathing apparatus when entering area unless atmosphere is proven to be safe. Stop leak if safe to do so.

6.2. Methods and materials for containment and cleaning up

Methods for cleaning up

: This material and its container must be disposed of in a safe way, and as per local legislation.

6.3. Reference to other sections

For further information refer to section 8: Exposure controls/personal protection

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g, wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in a cool, well-ventilated place. Store and use with adequate ventilation. Store only where temperature will not exceed 125°F (52°C). Firmly secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods

OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE: When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls

: Oxygen detectors should be used when asphyxiating gases may be released. Systems under pressure should be regularly checked for leakages. Provide adequate general and local exhaust ventilation. Consider work permit system e.g. for maintenance activities.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment

: Face shield. Safety glasses. Gloves.







Hand protection

: Wear work gloves when handling containers. Wear heavy rubber gloves where contact with product may occur.

EN (English) SDS ID : E-4563 3/7



Argon

Safety Data Sheet E-4563

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 08-03-2016 Supersedes: 10-15-2013

Eye protection

: Wear goggles and a face shield when transfilling or breaking transfer connections. Select in accordance with the current CSA standard Z94.3, "Industrial Eye and Face Protection", and any provincial regulations, local by

Respiratory protection

Respiratory protection: Use respirable fume respirator or air supplied respirator when working in confined space or where local exhaust or ventilation does not keep exposure below TLV. Select in accordance with provincial regulations, local bylaws or guidelines. Selection should be based on the current CSA standard Z94.4, "Selection, Care, and Use of Respirators." Respirators should also be approved by NIOSH and MSHA. For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus (SCBA).

Thermal hazard protection : None necessary.

Environmental exposure controls : None necessary.

Other information

Other protection: Safety shoes for general handling at customer sites. Metatarsal shoes and cuffless trousers for cylinder handling at packaging and filling plants. Select in accordance with the current CSA standard Z195, "Protective Foot Wear", and any provincial regulations, local bylaws or guidelines. For working with flammable and oxidizing materials, consider the use of flame resistant anti-static safety clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : Colourless gas.

Molecular mass : 40 g/mol
Colour : Colourless.

Odour : No odour warning properties.

Odour threshold : No data available
pH : Not applicable.
pH solution : No data available
Relative evaporation rate (butylacetate=1) : No data available
Relative evaporation rate (ether=1) : Not applicable.

Melting point : -189 °C

Freezing point : No data available

Boiling point : -185.9 °C

Flash point : No data available
Critical temperature : -122.4 °C
Auto-ignition temperature : Not applicable.
Decomposition temperature : No data available
Vapour pressure : Not applicable.
Vapour pressure at 50 °C : No data available

Critical pressure : 4898 kPa

Relative vapour density at 20 °C : 0.0016 (≥ 21.1)

Relative density : No data available

Relative density of saturated gas/air mixture : No data available

Density : Vapour density 0.103 lb/ft³ at 21.1°C (70°F)

Relative gas density : 1.38

Solubility : Water: 61 mg/l
Log Pow : Not applicable.
Log Kow : Not applicable.
Viscosity, kinematic : Not applicable.
Viscosity, dynamic : Not applicable.
Viscosity, kinematic (calculated value) (40 °C) : No data available
Explosive properties : Not applicable.

Oxidizing properties : None.

Flammability (solid, gas)

Non flammable

integrity or accuracy of any version of this document after it has been downloaded or removed from our website.

EN (English)

SDS ID : E-4563

4/7



Argon Safety Data Sheet E-4563

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 08-03-2016 Supersedes: 10-15-2013

Other information

Minimum ignition energy : ≈

Gas group : Compressed gas

Additional information : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below

ground level

SECTION 10: Stability and reactivity

10.1. Reactivity

: No reactivity hazard other than the effects described in sub-sections below. Reactivity

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : None.

Conditions to avoid None under recommended storage and handling conditions (see section 7).

Incompatible materials Using this product in welding and cutting may create additional hazards. The arc from electric

arc welding may form gaseous reaction products such as carbon monoxide and carbon dioxide. Ozone and nitrogen oxides may be formed by the radiation from the arc. Other decomposition products of arc welding and cutting originate from the volatilization, reaction, and oxidization of

the material being worked.

Hazardous decomposition products : None.

SECTION 11: Toxicological information

Likely routes of exposure : Inhalation.

Information on toxicological effects 11.1.

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

Skin corrosion/irritation : Not classified

pH: Not applicable.

Serious eye damage/irritation : Not classified

pH: Not applicable.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity Not classified

: Not classified Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified Specific target organ toxicity (repeated

exposure)

Aspiration hazard : Not classified

SECTION 12: Ecological information

Toxicity

: No ecological damage caused by this product. Ecology - general

Persistence and degradability 12.2.

Argon (7440-37-1)

Persistence and degradability No ecological damage caused by this product.

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.

EN (English) SDS ID: E-4563 5/7



Argon

Safety Data Sheet E-4563

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 08-03-2016 Supersedes: 10-15-2013

12.3. Bioaccumulative potential

Argon (7440-37-1)		
Log Pow	Not applicable.	
Log Kow	Not applicable.	
Bioaccumulative potential	No ecological damage caused by this product.	

12.4. Mobility in soil

Argon (7440-37-1)		
Mobility in soil	No data available.	
Log Pow	Not applicable.	
Log Kow	Not applicable.	
Ecology - soil	No ecological damage caused by this product.	

12.5. Other adverse effects

Effect on the ozone layer : None Effect on global warming : None

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : May be vented to atmosphere in a well ventilated place. Consult supplier for specific

recommendations. Do not discharge into any place where its accumulation could be

dangerous. Contact supplier if guidance is required.

Waste disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international

regulations. Contact supplier for any special requirements.

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

TDG

UN-No. (TDG) : UN1006

TDG Primary Hazard Classes : 2.2 - Class 2.2 - Non-Flammable, Non-Toxic Gas.

Proper shipping name : ARGON, COMPRESSED

Explosive Limit and Limited Quantity Index : 0.125 L Passenger Carrying Road Vehicle or Passenger : 75 L

Carrying Railway Vehicle Index

14.3. Air and sea transport

IMDG

UN-No. (IMDG) : 1006

Proper Shipping Name (IMDG) : ARGON, COMPRESSED

Class (IMDG) : 2 - Gases MFAG-No : 121

IATA

UN-No. (IATA) : 1006

Proper Shipping Name (IATA) : Argon, compressed

Class (IATA) : 2

SECTION 15: Regulatory information

15.1. National regulations

Argon (7440-37-1)

Listed on the Canadian DSL (Domestic Substances List)

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.

EN (English) SDS ID : E-4563 6/7



Argon Safety Data Sheet E-4563

according to the Hazardous Products Regulation (February 11, 2015)

Date of issue: 10-15-1979 Revision date: 08-03-2016 Supersedes: 10-15-2013

15.2. International regulations

Argon (7440-37-1)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on INSQ (Mexican national Inventory of Chemical Substances)

SECTION 16: Other information

: 15/10/1979 Date of issue Revision date : 03/08/2016 Supersedes : 15/10/2013

Indication of changes:

Other information

Training advice : The hazard of asphyxiation is often overlooked and must be stressed during operator training.

> Praxair asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information

> > The opinions expressed herein are those of qualified experts within Praxair Canada Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Praxair Canada Inc, it is the user's obligation to determine the conditions of safe use of the product. Praxair Canada Inc, SDSs are furnished on sale or delivery by Praxair Canada Inc, or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your Praxair sales representative, local distributor, or supplier, or download from www.praxair.ca. If you have questions regarding Praxair SDSs, would like the document number and date of the latest SDS, or would like the names of the Praxair suppliers in your area, phone or write Praxair Canada Inc, (Phone: 1-888-257-5149; Address: Praxair Canada Inc, 1 City Centre Drive, Suite 1200, Mississauga, Ontario, L5B 1M2).

> > PRAXAIR and the Flowing Airstream design are trademarks or registered trademarks of Praxair Technology, Inc. in the United States and/or other countries.

NFPA health hazard : 0 - Exposure under fire conditions would offer no hazard


beyond that of ordinary combustible materials.

NFPA fire hazard

NFPA reactivity 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.

NFPA specific hazard : SA - This denotes gases which are simple asphyxiants.



HMIS III Rating

Physical

Health : 0 Minimal Hazard - No significant risk to health Flammability : 0 Minimal Hazard - Materials that will not burn

> 3 Serious Hazard - Materials that may form explosive mixtures with water and are capable of detonation or explosive reaction in the presence of a strong initiating source. Materials may polymerize, decompose, self-react, or undergo other chemical change at normal temperature

and pressure with moderate risk of explosion

SDS Canada (GHS) - Praxair

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

This document is only controlled while on the Praxair Canada Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.

SDS ID: E-4563 EN (English) 7/7